



CADE/CAODC DRILLING CONFERENCE
October 23 & 24, 2001
Calgary, Alberta Canada



TITLE:	Practical Risk Assessment Techniques for Evaluating Borehole Instability	PAPER NO. 2001-08
AUTHOR(S):	Pat McLellan, Advanced Geotechnology Inc. Chris Hawkes, Advanced Geotechnology Inc.	Page 1 of 1

COPYRIGHT NOTATION: This paper was selected for presentation by the CADE/CAODC Drilling Conference Technical Committee, following a review of information contained in an abstract submitted by the author(s). Contents of the paper have not been reviewed by the Technical Committee and do not necessarily reflect the position of any or all of the Conference sponsors. Permission to copy is restricted to just this abstract page. Illustrations may not be copied. The abstract should contain conspicuous acknowledgement of where and by whom the paper was presented. Further permission to copy may be requested from the CADE/CAODC Technical Chairman, 800, 540 - 5 Avenue SW, Calgary, Alberta, Canada T2P 0M2.

ABSTRACT:

Drilling and completion problem costs are often associated with borehole instability in weak, fissile or reactive shales, especially in tectonically disturbed areas. Better well planning tools are required to determine the optimal window of bottomhole pressure or mud density and the best fluid properties for drilling vertical, horizontal and deviated wells that penetrate these rocks. A number of predictive models have been developed for assessing borehole instability risks, ranging from relatively simple linear elastic models through to more complex non-linear models that require numerical solution. In addition to selecting an appropriate model for a given borehole instability risk analysis, the accuracy and applicability of the model-based predictions depends heavily on the criteria used to identify the onset of unacceptable levels of borehole instability risk.

This paper will demonstrate the application of several different predictive models that are available in the *STABView* borehole stability analysis software package. Various instability risk criteria will be shown, including: shear yielding initiation at the borehole wall, cross-sectional area of rock yielding, average radius of the yielded zone, total volume of yielded rock for a given stratigraphic unit, total volume of yielded rock that detaches from the borehole wall, borehole breakout width or angle, rubble fill percentage for horizontal wells, borehole wall convergence or squeezing in plastic shales, and hole enlargement due to erosion. Advanced techniques for predicting yielded rock detachment will also be demonstrated using FLAC, a numerical geomechanical software program. Calibration techniques for developing practical instability risk estimates based on offset well experience will be shown with several field examples.